

ATTACHMENT 2

Table 2: WATER REQUIREMENTS FOR NON-R&R OPTIONS													
	Minimum Flows	340,000 CPM Floor				320,000 CPM Floor				286,000 CPM Floor			
		Deficit	Storage Needs without pulses	Deficit with Pulses	Storage Needs with Pulses	Deficit	Storage Needs without Pulses	Deficit with Pulses	Storage Needs With Pulses	Deficit	Storage Needs without Pulses	Deficit with Pulses	Storage Needs With Pulses
Comal Springs	30 cfs	65,400	111,180	99,800	169,660	39,400	66,980	65,400	111,180	16,100	27,370	31,772	54,012
	40 cfs	93,300	158,610	119,500	203,150	59,100	100,470	79,600	135,320	25,600	43,520	32,700	55,590
	50 cfs	123,300	209,610	144,600	245,820	82,500	140,250	98,500	167,450	38,600	65,620	53,800	91,460
San Marcos Springs	45 cfs	10,800	12,960	22,200	26,640	4,400	5,280	4,400	5,280	500	600	500	600
	55 cfs	19,800	23,760	31,700	38,040	9,000	10,800	16,200	19,440	2,700	3,240	2,700	3,240
	60 cfs	26,200	31,440	35,369	42,443	13,400	16,080	24,000	28,800	4,700	5,640	11,200	13,440
	75 cfs	54,600	65,520	57,305	68,766	37,200	44,640	40,000	48,000	23,300	27,960	26,900	32,280